

Sewing Pattern — Dress 5130

Recommendations on fabric: fabric suitable for dress, e.g. cotton, viscose, artificial silk.

You will also need: fusing, 4 buttons.

Seam allowances are included if the pattern has double contour.

Seam allowances are NOT included if your pattern has single contour and need to be added when laying out and cutting details. All seams 1 cm, 2 cm for hem.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. back upper part – 1 piece
2. back middle lower part – 2 pieces
3. back side lower part – 2 pieces
4. back side part – 2 pieces
5. front side lower part – 2 pieces
6. front middle lower part (flying) – 2 pieces
7. front side upper part 1 – 2 pieces
8. upper flying part – 2 pieces
9. sleeve – 2 pieces
10. back neckline facing – 1 piece
11. facing of flying detail – 2 pieces

Decorative fabric:

1. front side lower part – 2 pieces
2. front middle lower part – 1 piece
3. front side upper part – 2 pieces
4. front upper part – 2 pieces
5. front part facing – 2 pieces
6. shoulder pad – 2 pieces

INSTRUCTIONS:

1. sew back darts. sew edges of back upper and back lower parts. sew relieve edges to notch marks.
2. oversew upper flying part with facing. sew edges of front upper flying part and front lower flying part. sew relieve edges to notch mark. sew edges of relieves of front upper parts. sew back shoulder edges and front shoulder edges.
3. facings and neckline: apply the fusing to wrong side of back neckline facing and front part facing. sew back neckline facings together, sew them to front facings, press seams. neaten inner edges of neckline facings and front facings. overstretch neckline and edgings with facings, then topstitch at 0.5 cm from the edge; press.
4. sew edges of front lower parts. sew front lower part and front upper part.
5. sleeves. press sleeves lower edges. sew sleeve hems by hand. sew sleeves into armholes coinciding edges of front armhole and front flying parts and gathering along the sleeve caps, coinciding ceases. neaten edges of sleeves and armholes.
6. sew garment hem.
7. make buttonholes and sew buttons.

TECHNICAL DRAWING:

